

**This Page Is Inserted by IFW Operations  
and is not a part of the Official Record**

## **BEST AVAILABLE IMAGES**

**Defective images within this document are accurate representations of  
the original documents submitted by the applicant.**

**Defects in the images may include (but are not limited to):**

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

## Patent Abstracts of Japan

PUBLICATION NUMBER : 08167413  
PUBLICATION DATE : 25-06-96


APPLICATION DATE : 12-12-94  
APPLICATION NUMBER : 06307399

APPLICANT : MATSUSHITA ELECTRIC IND CO LTD;

INVENTOR : MIURA KUNIHIDE;

INT.CL. : H01M 4/58 H01M 4/06 H01M 6/16

TITLE : NONAQUEOUS ELECTROLYTE  
BATTERY



ABSTRACT : PURPOSE: To improve liquid absorptivity and electric conductivity of positive electrode pellet, and heighten a discharge characteristic by coating a positive electrode active material with expanded graphite.

CONSTITUTION: Lithium 3 being a negative electrode active material is press-fitted to an inner wall of a sealing plate 2 also serving as a negative electrode terminal. An opening tip part of a battery case 1 also serving as a positive electrode terminal is calked inward and the peripheral edge of the sealing plate 2 is so fastened through a gasket 4 that a port is sealed. A positive electrode active material is coated with expanded graphite having an average particle diameter of 20 $\mu$ m to 80 $\mu$ m being a conductive material having binding performance, and is used as a positive electrode pellet 6 in which a binding agent such as a fluororesin does not substantially exist. So, a uniform mixed condition is held, and the positive electrode pellet can be molded without adding a binding agent.

COPYRIGHT: (C) JPO